

MARK® T 682

Description	Octyltin maleate stabiliser
Delivery form	Clear, yellowish, low viscosity liquid
Specification	The specified values are given in the Product Specification.
Application	<p>MARK® T 682 is mainly used in the production of rigid PVC packaging materials to comply with food regulations. MARK® T 682 is especially suited for extrusion blow moulding of very thin, almost odourless packaging film with excellent transparency. This application requires a careful adjustment of lubricants and processing aids.</p> <p>MARK® T 682 is also used for prestabilising PVC in the polymerisation reactor. At concentrations of 0.1 - 0.3 phr the thermal decomposition during the monomer stripping process of the polymer can be considerably reduced.</p> <p>PVC resin prestabilised with MARK® T 682 shows no staining by applying the commonly used thermostabilisers during processing.</p> <p>During processing of organotin maleates in open systems volatile reaction products causing irritations of the mucous membranes may be liberated and the use of effective exhaustors is recommended.</p> <p>A comparison of the property profiles of the different MARK® octyltin standard products is given in our product survey (Additives for PVC Processing).</p>
Approval	MARK® T 682 is approved in many countries for the stabilisation of rigid PVC packaging materials. For details please refer to our separate positive list.
Dosage	Recommended concentration: 1.2 phr
Packaging	MARK® T 682 is supplied in standard steel lid drums, which can be reused and recycled and which conform to the UN regulations (contents 220 kg), as well as in recyclable IBC (intermediate bulk containers, content: 1000 kg).

The information contained herein relates to a specific Galata product and its use, and is based on information available as of the date hereof. Additional information relating to the product can be obtained from the pertinent Material Safety Data Sheets. Nothing in this Technical Data Sheet shall be construed to modify any of Galata standard terms and conditions of sale under which the product is sold by Galata. NOTHING IN THIS TECHNICAL DATA SHEET SHALL BE CONSTRUED TO CONSTITUTE A REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE PRODUCT'S CHARACTERISTICS, USE, QUALITY, SAFETY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall constitute permission or recommendation to practice any intellectual property without the permission of the owner.

Galata Chemicals GmbH

Chemiestrasse 22, D-68623 Lampertheim, ☎ +49 (0) 6206 9570, fax +49 (0) 6206 95 7109

Storage

Recommended storage temperature: 15 to 30 °C.

Keep containers dry and reseal tightly after use.

The product has the tendency to form a precipitation of solid dioctyltinmaleate; small amounts however do not affect the efficiency of the stabiliser.

Version 11/10

Mark[®] is a trademark of Galata Chemicals GmbH.

The information contained herein relates to a specific Galata product and its use, and is based on information available as of the date hereof. Additional information relating to the product can be obtained from the pertinent Material Safety Data Sheets. Nothing in this Technical Data Sheet shall be construed to modify any of Galata standard terms and conditions of sale under which the product is sold by Galata. NOTHING IN THIS TECHNICAL DATA SHEET SHALL BE CONSTRUED TO CONSTITUTE A REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE PRODUCT'S CHARACTERISTICS, USE, QUALITY, SAFETY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall constitute permission or recommendation to practice any intellectual property without the permission of the owner.